

Product Discontinuance Notification—PDN# 0000362264
April 15, 2022

Dear Valued Customer,

We would like to inform you that Moxa is going to discontinue the OnCell G3150A-LTE-EU Series and OnCell G3470A-LTE-EU Series. This process will effectively begin from May 1, 2022.

If you need any of these discontinued products for an existing project, please contact your Moxa sales representative to place orders before January 31, 2023. Also, please note that last-buy orders may be subject to availability.

Please review the details below to determine how these discontinuances will affect your products and/or operations.

Which products will be discontinued?

The following products will be discontinued. Also, see the models recommended to replace the soon to-be-discontinued models, as well as when the replacement models will be available for order.

Discontinued	Recommended Replacement	Available for Order
OnCell G3150A-LTE-EU	OnCell G4302-LTE4-EU	Q2, 2023
OnCell G3150A-LTE-EU-T	OnCell G4302-LTE4-EU-T	Q2, 2023
OnCell G3470A-LTE-EU	OnCell G4302-LTE4-EU (+ EDS switch for port extension)	Q2, 2023
	OnCell G4308-LTE4-EU	Q4, 2023
OnCell G3470A-LTE-EU-T	OnCell G4302-LTE4-EU-T (+ EDS switch for port extension)	Q2, 2023
	OnCell G4308-LTE4-EU-T	Q4, 2023

Applicable differences in specifications

In this table, we list the difference in specifications between the discontinued products and the recommended replacement products.

Specification	OnCell G3150A-LTE-EU Series (Discontinued)	OnCell G4302-LTE4-EU Series (Replacement)
LTE Band	B1, B3, B7, B8, B20	B1, B3, B7, B8, B20, B28
LTE Category	Cat 3 (100 Mbps DL, 50 Mbps UL)	Cat 4 (150 Mbps DL, 50 Mbps UL)
Ethernet	1 FE	2 GE (1 WAN configurable)
DI/DO	2DI, 1DO	1DI, 1DO
USB	-	1 Type A for ABC-02

SIMs Slot	2 Mini-SIM (2FF)	2 Nano-SIM (4FF)
GNSS	GPS, GLONASS	GPS, GLONASS, Galileo, BeiDou
WAN Redundancy	Dual SIM	Dual SIM, Eth WAN/Cellular Redundancy, VRRP
Routing	-	Static Route
Security	Firewall, NAT, IPsec, OpenVPN	Firewall, NAT, IPsec, DMZ, DOS Prevention, Malformed Packet Filtering, 802.1X Network Access Control, Radius Authentication, Secure Boot
Dimensions	126 x 30 x 107.5 mm	125 x 46.2 x 100 mm
Operating Temperature	Standard: 0 to 55°C Wide Temp.: -30 to 70°C	Standard: -10 to 55°C Wide Temp.: -30 to 70°C

Specification	OnCell G3470A-LTE-EU Series (Discontinued)	OnCell G4302-LTE4-EU Series OnCell G4308-LTE4-EU Series (Replacement)
LTE Band	B1, B3, B7, B8, B20	B1, B3, B7, B8, B20, B28
LTE Category	Cat 3 (100 Mbps DL, 50 Mbps UL)	Cat 4 (150 Mbps DL, 50 Mbps UL)
Ethernet	4 GE	G4302: 2 GE (1 WAN configurable) G4308: 8 GE (1 WAN configurable)
DI/DO	1DI, 1DO	1DI, 1DO
USB	-	1 Type A for ABC-02
SIMs Slot	2 Mini-SIM (2FF)	2 Nano-SIM (4FF)
GNSS	GPS, GLONASS	GPS, GLONASS, Galileo, BeiDou
WAN Redundancy	Dual SIM	Dual SIM, Eth WAN/Cellular Redundancy, VRRP
Routing	-	Static Route
Security	Firewall, NAT, IPsec	Firewall, NAT, IPsec, DMZ, DOS Prevention, Malformed Packet Filtering, 802.1X Network Access Control, Radius Authentication, Secure Boot
Dimensions	124 x 66.3 x 90 mm	125 x 46.2 x 100 mm
Operating Temperature	Standard: 0 to 55°C Wide Temp.: -30 to 70°C	Standard: -10 to 55°C Wide Temp.: -30 to 70°C

Please note that all service rules (e.g., warranty) still apply to discontinued products.

If you have any questions, please contact Yin Chang at YinY.Chang@moxa.com, or contact your regional sales representative.